

Pendant lights

SPECIAL LINE P56

Steel cable suspension
individually shortenable



SKU: 589-56.96sd

Drawbar suspension
50 - 150cm (height adjustable)



SKU: 589-56.95sd

 RAL 9006 /silber

TECHNICAL DATA

V	220-240
Hz	50-60
W	56 / 112
Lm	7326
K	5700
Lux	8700 (50cm)
CRI	> 95 (typ. 97)
kg	3,9 / 6,3
RG	0

Material:	Extruded aluminium
Insert:	Single / double workstation
Dimming:	Push-button (ON/OFF/DIM) / 1-100%
Lifetime:	50.000h
Warranty:	2 years
LED Cover:	Microprismatic lens/plus additional high-tech diffuser foil
Power connection:	luster terminals in right canopy
LED Driver:	Tridonic
Colour:	Silver
Dimensions:	930 x 150 x 35,5 mm (LxWxH) 1950 x 150 x 35,5 mm (LxWxH)



Distance:	Illuminance:
80 cm	4300 Lux
70 cm	5350 Lux
60 cm	6700 Lux
50 cm	8700 Lux

Work surface

HIGHLIGHTS

- ✓ No colour location shifts when dimming the LEDs
- ✓ No UV and infrared components in the light spectrum (prevents e.g. premature hardening of plastics)
- ✓ No heat load in the direction of light emission - only slight heating of the luminaire surface
- ✓ Extremely bright with simultaneous large-area illumination thanks to three parallel LED chambers - up to 8700lx illuminance at a distance of 50 cm
- ✓ Optical design package: also available with filigree steel cable suspensions and transparent insulated supply cable (not infinitely height-adjustable)



OPTIONAL

Double workplace



Dimension: 1950 x 150 x 35,5 mm (LxWxH)

Suspension: only steel cable suspension

SKU: 589-112.96sd (steel cable suspension)

Zum Weiherlein 16
97509 Kolitzheim
Germany

Sales: +49(0)15128033591
info@rmd-leuchten.de
www.rmd-leuchten.de

